

GOOCARS HEMI

▲ SPECIFICATIONS 15inch 2PIECE/NORMAL

SIZE	STANDARD				DEEP RIM			
	A - Disk 4H-100				O - Disk 4H-100			
	(Lip Size) mm				(Lip Size) mm			
	Standard Offsets		Offset Range		Standard Offsets		Offset Range	
15 × 5.5J				33(46) ~ 11(68)	42(47)			43(46) ~ 21(68)
15 × 6.5J	45(46)	35(56)	25(66)	45(46) ~ 19(72)				55(46) ~ 29(72)
15 × 7.0J	45(53)	35(63)	25(73)	52(46) ~ 12(86)				62(46) ~ 22(86)
15 × 7.5J	45(59)	35(69)	25(79)	58(46) ~ 6(98)				68(46) ~ 16(98)
15 × 8.0J	45(65)	35(75)	25(85)	64(46) ~ 0(110)				74(46) ~ 10(110)
15 × 8.5J	45(72)	35(82)	25(92)	71(46) ~ -6(123)				81(46) ~ 4(123)
15 × 9.0J	45(78)	35(88)	25(98)	77(46) ~ -13(136)				87(46) ~ -3(136)
15 × 9.5J	45(84)	35(94)	25(104)	83(46) ~ -19(148)				93(46) ~ -9(148)
15 × 10.0J	45(91)	35(101)	25(111)	90(46) ~ -26(162)				100(46) ~ -16(162)

● Available finishes: Bright Buff Finish (BBF)

● Included accessories: (1) Center Cap / (1) Valvestem (15inch - V07C)

※ 15 inch center disc will protrude past the rim flange when the lip size is less than 52mm